

MOBILE SERIES

- Auto-Protection Function Independent
- Dehumidifying Function
- Microprocessor Control
- Rotary Compressor
- Exchangeable Filter
- 24-hours Timer
- Environmentally Friendly
- 2-year Warranty

AMC-09C
AMC-14Aa



AMC-09C

AMC-14Aa



Powerful Japanese Compressor Technology

Mould-Proof Air Filter

Low Voltage Start Up

Environmentally Friendly

Environmentally Friendly

SPECIFICATIONS

LINE		MOBILE SERIES		
MODEL		AMC-09C		AMC-14Aa
Capacity	Cooling		2,5	4,1
Power supply		kW		
		Hz	50	50
Rated current		V	220-240	220-240
		A	7,0	10,6
Power input		W	1200	1700
EER		W/W	2,2	2,0
Noise level	Max	dB(A)	49-51-55	55-57-59
Air flow		m ³ /hr	440	570
Dehumidifying volume		Li/hr	2,2	1,6
Refrigerant		Type	R407C	R410A
Refrigerant charge		g	590	1100
Dimensions (w x h x d)		mm	450x840x370	546x840x405
Net weight		kg	31	47
Operation temperature range Max / Min				
Cooling		°C	43~16	43~16



QUIET DESIGN

With aided computer design changing the aerodynamics the air flow noise is significantly lower.



DRY MOULD PROOF AMC-14Aa

This function prevents dry/wet mould forming by keeping the internal fan running until the unit expels any remaining moisture in the condenser.

LOW VOLTAGE START UP

Even with Low voltage at 185V the Sinclair Mobile series can still safely start and operate.