






OUTDOOR UNIT

	Capacity (HP)	Model	Combination (HP)	Indoor unit	
	4	SDV-120EA	4	6	
	4	SDV-120EA-3	4	6	
	6	SDV-140EA	6	8	
	8	SDV-252EA	8	13	
	10	SDV-280EA	10	16	
	12	SDV-335EA	12	16	
	14	SDV-400EA	14	16	
	16	SDV-450EA	16	20	
		18	SDV-532EA	8+10	20
20		SDV-560EA	10+10	20	
22		SDV-615EA	10+12	20	
24		SDV-680EA	10+14	20	
26		SDV-730EA	10+16	20	
28		SDV-785EA	12+16	20	
30		SDV-850EA	14+16	32	
32		SDV-900EA	16+16	32	
		34	SDV-960EA	10x2+14	32
		36	SDV-1010EA	10x2+16	32
	38	SDV-1065EA	10+12+16	32	
	40	SDV-1130EA	10+14+16	40	
	42	SDV-1180EA	10+16x2	40	
	44	SDV-1235EA	12+16x2	40	
	46	SDV-1300EA	14+16x2	40	
	48	SDV-1350EA	16x3	40	
	50	SDV-1405EA	12x3+14	50	
	52	SDV-1455EA	12x3+16	50	
	54	SDV-1520EA	12x2+14+16	50	
	56	SDV-1570EA	12x2+16x2	50	
	58	SDV-1630EA	10+16x3	50	
	60	SDV-1685EA	12+16x3	64	
	62	SDV-1750EA	14+16x3	64	
	64	SDV-1800EA	16x4	64	

Model	SDV-	120EA	120EA-3	140EA	252EA	280EA	335EA	400EA	450EA
Capacity									
Cooling	kW	12	←	14	25,2	28	33,5	40	45
Heating	kW	14	←	16	27	31,5	35	43	47
Electrical Data									
Voltage, Frequency, Phase	V~, Hz, f	220-240, 50, 1	380-400, 50, 3	←	←	←	←	←	←
Performance									
Air Flow Volume	m ³	6000	←	←	11500	←	←	14800	←
Noise Level	dB(A)	55	←	←	58	←	←	60	←
Dimension									
Net W×H×D	mm	940x1245x340	←	940x1245x340	980x1630x800	←	←	1380x1630x830	←
Packing W×H×D	mm	1058x1380x435	←	1058x1300x435	1040x1780x840	←	←	1440x1800x860	←
Weight									
Net	kg	112	117	117	245	←	←	382	←
Gross	kg	125	126	126	260	←	←	400	←
Piping Connection									
Max Length of pipe		50	←	70	175	←	←	←	←
Max Height Difference Between indoor units		8	←	←	15	←	←	←	←
Between indoor units and outdoor unit		20	←	←	70	←	←	←	←

Remarks: 1. The above specifications are subject to change without prior notice for product improvement.
 2. The noise levels given in the table reflect the levels in anechoic chamber.
 3. SDV-120EA, SDV-120EA-3 and SDV-140EA are not modular.